



range of Hose Pipes



IS : 8423



CRC CP Cool Hose

Controlled Percolating Hose

CP Cool Hose is Controlled Percolating Hose with a unique construction to ensure continuous oozing of water all around the jacket in a controlled manner whilst the built up pressure inside the hose is not lost. These hoses are used when the hoses are needed to pass through the flames and come in contact with fire. The stringent flame resistant test required under to IS . 8423 ensures that the hoses when tested with a lighted blow lamp on a specimen of hose under water pressure do not fail.

These hoses are excellent in fighting fires specially in coal mines, textiles mills, refineries and high rise buildings.

PROPERTIES

- Cotton Synthetic Fibre
- Circularly Woven Jacketed
- Abrasion Resistant
- Ultra Thin Lining
- Outstanding Adhesion
- Light, flexible, compact, flat folding
- High Kink Resistance

PRESSURE RATINGS

Burst pressure 36kg/cm² (530 psi)
 Proof pressure 22kg/cm² (320 psi)
 Working pressure 18kg/cm² (260 psi)

SPECIFICATIONS

IS 8423/1994 • TAC Approved • Bearing ISI mark

SIZES

38mm • 50mm • 63mm • 70mm

APPLICATIONS

- Fire Brigade • Refineries • Industrial Plants
- Power Plants • Textile Mills
- High Rise Buildings • Coal Mines

LENGTHS

15mtrs • 18.3mtrs • 22.5mtrs • 30mtrs