

Aqualine Fire Hose



ISI Marked EPDM Fire Hoses



CONSTRUCTION

Fully synthetic high tenacity jacket to withstand repeated pressure surges.

INNER LINING

Ultra light weight synthetic EPDM Rubber lining having low friction loss to eliminate tackiness or cracks during lifetime of hose.

CHARACTERISTICS

100% synthetic construction having:

- Resistance to sea-water and ozone

- Resistance to hot climatic conditions, fungus and rot
- Pressure ratings as per IS:636
- Flexible, Compact and Easy to Clean
- Colour : Silver White

STANDARD LENGTHS

15mtr, 18.3mtr, 22.5mtr and 30mtr

APPLICATIONS

- Highrise buildings
- De-watering
- Medium pressure fire fighting operation
- And other industries
- Steel Plants
- Construction work

APPROVALS

- ISI Marked under IS: 636/1988 Type A

Size mm / inches	Max Wt gm / mtr	Working Pressure psi	Proof Pressure psi	Burst Pressure psi
38 / 1 1/2"	255	260	320	600
50 / 2"	330	260	320	600
63.5 / 2 1/2"	410	260	320	575
70 / 2 3/4"	460	260	320	575
76 / 3"	470	260	320	550



CHHATARIYA FIRETECH INDUSTRIES

23A SURYODAYA MILLS COMPOUND | 96 TARDEO ROAD
MUMBAI 400 034 | INDIA
PH 91 22 23513705 / 23521313 / 23510849 | FAX 91 22 23510400
E-MAIL chhatariya@vsnl.com | URL www.chhatariya.com

FACTORY :
89 GIDC ESTATE, MAHUVA 364 290, GUJARAT, INDIA
PH +91 2844 228887 / 228749 | FAX 91 2844 246287
E-MAIL cfi_52@yahoo.co.in | URL www.chhatariyafiretech.com